

Definition / Tanımlama

PURINATE RP 102 is a MDI based, medium reactivity and viscosity polyurethane prepolymer material containing 100% solids.

Application Area / Uygulama Yeri

PURINATE RP 102 is solvent free, has strong adhesion, medium viscosity and suitable drying time.

Advantages / Avantajlar

- Contains 100% solids
- It has a fast drying time
- It has high performance

Technical Properties / Teknik Özellikler

No	Test / Analiz	Result / Sonuç	Unit / Birim	Test Code
1	Appearance	Amber-Yellow	-	
2	Density	1,05-1,10	g/cm3 (23°C)	ISO 2811
3	Viscosity	900-1100	cP (23°C)	ASTM 2196
4	Solid content	100	%	ISO 3251

Packing / Paketleme

PURINATE RP 102 is shipped in 200kg metal drums.

Storage / Depolama

Products should be protected from high temperature and frost. The optimum storage temperature is between +5oC and +30oC. It is not suitable to be stored below or above this temperature and its shelf life will be shortened.

Safety and Health / Güvenlik ve Sağlık

The product should not come into contact with the skin and especially the eyes. Always use glasses to prevent contact with your eyes. In case of contact with your skin, wash with plenty of water. In case of irritation, seek medical advice immediately.

Note

The information on this data sheet is based on our experiences and correct to the best of our knowledge. It is, however, not binding. It has to be adjusted to the individual structure, application purpose and especially to local conditions. Our data refers to the accepted engineering rules, which have to be observed during application. This provided we are liable for the correctness of this data within the scope of our terms and conditions of sale-delivery-and-service. Recommendations of our employees which differ from the data contained in our information sheets are only binding if given in written form. The accepted engineering rules must be observed at all times.

Bu teknik formdaki veriler kendi deneyimlerimiz ve bilgilerimiz referans alınarak hazırlanmıştır. Ancak bağlayıcılığı yoktur. Yapıya, uygulama amacına ve özellikle yerel koşullara göre ayarlanmalıdır. Verilerimiz, uygulama sırasında uyulması gereken mühendislik kurallarını referans almıştır. Satış teslim, hizmet şartlarımız ve koşullarımız kapsamında bu verilerin doğruluğundan sorumlu olmaktayız. Çalışanlarımızın bilgilendirme formlarımızdaki yer alan verilerden farklı önerileri ancak yazılı olarak verilmesi halinde bağlayıcıdır. Kabul edilen mühendislik kurallarına her zaman uyulmalıdır.

**PURIN[®]Aqua****PURIN[®]ATE****PURIN[®]COAT PURIN[®]ADHE PURIN[®]SEAL PURIN[®]ELAS**