

Definition / Tanımlama

PURINATE SA 201 is a high reactivity, MDI-based product with medium viscosity and 100% solids content.

Application Area / Uygulama Yeri

PURINATE SA 201 is designed as a solvent-free sponge adhesive. With its strong adhesion, medium viscosity and suitable open time properties, it is used in sponge-sponge, sponge-felt bonding processes.

Advantages / Avantajlar

- 100% solids content
- Fast drying time
- High adhesion performance

Technical Properties / Teknik Özellikler

No	Test / Analiz	Result / Sonuç	Unit / Birim	Test Code
	Appearance	Amber	-	
	Viscosity	4.000 - 6.000	cP (23°C)	ASTM 2196
	Density	1,12 - 1,16	g/cm3 (23°C)	ISO 2811
	Solid content	100	%	ISO 3251

Packing / Paketleme

The product is shipped in 200kg metal drums, 60kg plastic drums or 20kg metal cans.

Storage / Depolama

Products should be protected from high temperatures and frost. The optimum storage temperature is between +5oC and +30oC. Storage below and above this temperature is not suitable and will shorten the shelf life.

Safety and Health / Güvenlik ve Sağlık

- Avoid getting on your skin and especially in your eyes
- Avoid contact of the product with water.
- In contact with water, it will react and foam and form CO2 gas, do not inhale.
- Always clean glue contamination immediately
- Protect from high temperatures

Note

The information on this data sheet is based on our experiences and correct to the best of our knowledge. It is, however, not binding. It has to be adjusted to the individual structure, application purpose and especially to local conditions. Our data refers to the accepted engineering rules, which have to be observed during application. This provided we are liable for the correctness of this data within the scope of our terms and conditions of sale-delivery-and-service. Recommendations of our employees which differ from the data contained in our information sheets are only binding if given in written form. The accepted engineering rules must be observed at all times.

Bu teknik formdaki veriler kendi deneyimlerimiz ve bilgilerimiz referans alınarak hazırlanmıştır. Ancak bağlayıcılığı yoktur. Yapıya, uygulama amacına ve özellikle yerel koşullara göre ayarlanmalıdır. Verilerimiz, uygulama sırasında uyulması gereken mühendislik kurallarını referans almıştır. Satış teslim, hizmet şartlarımız ve koşullarımız kapsamında bu verilerin doğruluğundan sorumlu olmaktayız. Çalışanlarımızın bilgilendirme formlarımızdaki yer alan verilerden farklı önerileri ancak yazılı olarak verilmesi halinde bağlayıcıdır. Kabul edilen mühendislik kurallarına her zaman uyulmalıdır.

**PURIN[®]Aqua****PURIN[®]ATE****PURIN[®]COAT PURIN[®]ADHE PURIN[®]SEAL PURIN[®]ELAS**